

## EAZECEL™ CTA3120 CELLULOSE ETHER

Eazeecel™ CTA3120 has been developed to improve the workability properties of tile cement adhesive, The special modification provide the good balance of the good workability for fresh mortar and the strengthen develop of hardened mortar, It is specially recommend in C1T series formulation

- ✓ High water retention
- ✓ Good workability
- ✓ Good anti-sagging properties
- ✓ Less influence on setting behavior for cement

### Characteristics of Eazeecel™ CTA3120

Viscosity :	approximately 40.000 mPas*
Particle size :	fine powder
Moisture content :	max. 8%
Bulk density :	200 - 500 g/l

2 % solution; on dry basis; Brookfield RVT; 20°C;20 rpm.

### Packaging and Storage

Eazeecel™ CTA 3120 is packed in multiply paper bags with an inner polyethylene bag. Net weight 20 Kg for all market . recommend emptying the bags from bottom. The empty bags can be recycled or burned. In unopened bags, Eazeecel™ CTA3120 can be stored for several years. In opened bags, the moisture content of Eazeecel™ CTA3120 will be influenced by the air humidity.

At the temperatures above 250°C, charring of Eazeecel™ CTA3120 will occur. At high temperatures and in contact with an open flame, Eazeecel™ CTA3120 will burn slowly with the characteristic of cellulose.

### Product Safety

Please read and understand the Safety Data Sheet (SDS) before using this product.